



| BALAMAN SPECIFICATIONS | |
|------------------------|--|
| MODEL | U2BMF-150W |
| MAX.LOAD | 142kg (BELOW POINT A) 125kg (BELOW POINT B) |
| MAX.RADIUS | R2240 mm |
| HORIZONTAL STROKE | 1715 mm |
| VERTICAL STROKE | 1520 mm |
| MAX.WORKING HEIGHT | 2020 mm |
| MAX.MACHINE HEIGHT | 3487 mm |
| AIR SUPPLY | 0.54 MPaG |
| AIR CONSUMPTION | 181L/min (10 SEC CYCLE) |
| POWER SUPPLY | SINGLE-PHASE AC85~AC264V 50/60Hz 0.1KVA |
| CONTROL METHOD | |
| COATING | MAIN BODY & BASE DIC233(DIC No.) 5Y8/1(MUNSELL No.) ATTCHMENT 10R5.5/14.5 (MUNSELL No.) |
| MAIN UNIT MASS | APPROX. 275kg |
| BASE UNIT MASS | APPROX. 130kg |
| SWIVEL UNIT MASS | 5kg |
| RELAY BOX MASS | 12kg |
| WORK PIECE MASS | kg |
| REMARKS | ACCESSORIES:PRESSURE REDUCE SET :POWER SUPPLY BOX |